



L2 SERIES Line Interactive Ups

1000 VA - 1500 VA - 2000 VA

GENERAL FEATURES / GENEL ÖZELLİKLER

- RS 232 Communication Port
- Wide input voltage range
- Short circuit and overload protection
- Battery start feature (Cold start)
- Advanced battery management
- Operation principle with low failure by clearing unnecessary details
- Compliance with local and international standards
- Wide range of spare part and 7/24 technical support
- Supply guarantee of 2 years for system and 10 years for spare part

- *RS 232 Haberleşme portu*
- *Geniş giriş gerilim aralığı*
- *Akım koruma ve aşırı yük koruması*
- *Aküden start özelliği (cold start)*
- *Akıllı akü yönetimi*
- *Gereksiz detaylardan arındırılmış çalışma prensibi*
- *Yerel ve uluslararası standartlara uygunluk*
- *Geniş yedek malzeme ağı ve 7/24 teknik servis desteği*
- *2 yıl sistem 10 yıl yedek parça temin garantisi*

L2 SERIES

Line Interactive Ups

1000 VA - 1500 VA - 2000 VA

Model	L2 1000 VA	L2 1500 VA	L2 2000 VA
Capacity KVA / Watt	1000 VA : 600 Watt	1500 VA : 900 Watt	2000 VA : 1200 Watt
Input	Voltage	220 V AC , +/- % 25	
	Frequence	50 Hz / 60 Hz +/- %10	
Output	Voltage	220 / 230 / 240 V AC (+/- %5)	
	Frequence	50 / 60 Hz. %1	
Output wave type	Line Interactive Mod		
Battery feeding time	5/15 Dk.		
Battery type	Dry-type battery group without requirement for maintenance		
Battery pieces	2 x 12V 07 Ah	2 x 12V 7.2 Ah	2 x 12V 09 Ah
Total battery Dc voltage	24 Vdc		
Battery Charge Time	5 hours from empty to 90% loading		
Transfer Time	2 to 4 mili second		
Overload capacity	%110 to %150 load 30 sec. %150 to big load 10 sec.		
Communi. interface	RS 232 Commnication Port and SNMP (Optional)		
Operation Temperature	0-40 C°		
Storage Temperature	25 C° ile 70 C°		
Humidity	0-95% (condensed relative humidity)		
Max. Operation Height	2000 m		
Protection Class	IP 20		
Noise Level	< 40 dBA		
Sizes (WxDxH) mm.	146 x 360 x 164		

* Celta reserves right to amend the data herein without notification