



APC C SERIES

1 Phase Input
1 Phase Output
Online Ups

5 KVA - 6 KVA - 10 KVA

GENERAL FEATURES / GENEL ÖZELLİKLER

- Automatic internal bypass
- Intelligent battery management
- Hot-swappable battery packs
- Parallel redundancy
- Manageability over the network
- Automatically restart of loads
- Cold start
- Resettable circuit breaker
- Compliance with international standards
- Serial connectivity
- Plug & play external batteries
- Preventive bugs
- Audible alarms
- Otomatik dahili baypass
- Akıllı akü yönetimi
- Çalışırken değiştirilebilir akü paketleri
- Paralel yedeklilik
- Ağ üzerinden yönetilebilirlik
- Yüklerin otomatik olarak yeniden başlatılması
- Cold start özelliği
- Resetlenebilir devre kesici
- Uluslararası standartlara uygunluk
- Seri bağlanabilirlik
- Tak ve çalıştır harici aküler
- Önleyici hata bildirimini
- Sesli alarmlar

APC C SERIES

1 Phase Input 1 Phase Output Online Ups

5 KVA - 6 KVA - 10 KVA

Model	SRC5000XLI	SRC6000XLI	SRC6000XLI
Capacity KVA / Watt	5 KVA / 3500 Watt	6 KVA / 4800 Watt	10 KVA / 8000 Watt
Parallel Operation up to 3 pieces	15 KVA / 10500 Watt	18 KVA / 14400 Watt	30 KVA / 24000 Watt
Input	Voltage	170 - 280 V AC , 1 Phase + Neutral	
	Frequence	46-70 Hz	
	Power Factor	0,99	
Output	Voltage	220 V AC (+/- %1)	
	Frequence	50 Hz. %1	
Output wave type	Automatic Internal By-pass		
Battery charge flow	750 Watt		960 Watt
Battery type	Dry-type battery group without requirement for maintenance		
Battery pieces	16		20
Total battery DC voltage	192 Vdc		240 Vdc
Battery Charge Time	5 hours from empty to 90% loading		
Transfer Time	0 sn.		
Overload capacity	5 min. in %105 and %125 load; 1 min. in %125 and %135 load; 10 sec. above %135		
System performance	90%		
Crest Factor	3:1		
THD	Linear Load	< 3 %	
	Non-Linear Load	< 5 %	
Communi. Interface	RS 232 Commun. Port and SNMP (Optional)		
Operation Temperature	0-40 C°		
Storage Temperature	25 C° ile 70 C°		
Humidity	0-95% (Non-condensed relative humidity)		
Max. Operation Height	2000 m		
Protection Class	IP 20		
Electromagnetic Compliance	EMS : IEC61000-4-2(ESD) IEC61000-4-3 (RS) IEC61000-4-4(EFT) IEC61000-4-5 (SURGE) EMI IEC62040-2 CLASS B		
Noise Level	< 55 dBA		
Sizes (WxDxH) mm.	670 x 440 x 88,5		628 x 440 x 131
Net Weight (Kg)	16	17	22

* Celta reserves right to amend the data herein without notification